

HydroSense 4410-OCM Oil Content Monitor



The Hydrosense 4410-OCM is a flow-through real-time monitor for on-line ppm (mg/l) indication of petroleum and/or non-petroleum oil in water.

The unique sensor design can optionally provide both fluorescence and light scatter simultaneously in one unit .

Fluorescence responds to dissolved and free (bouyant) hydrocarbons in water. This technology targets the aromatic hydrocarbons in the water and through a site calibration, correlates this to total oil.

Light Scatter can be used for turbidity indication or indication of free oils of any type, such as synthetic and vegetable.

The closed loop sample stream assembly communicates with the controller using a Modbus interface. This allows the sensor to be mounted remotely with two main benefits. 1) The sensor can be mounted close to the process to reduce lag time and, 2) The controller can be mounted in an area better suited to safe operator access and control wiring interface.

Ideal for:

- oil/water separators, FWKO and treater effluents
- produced water
- cooling water
- de-salination and RO systems
- water treatment
- stormwater run-off



* shown without enclosure on flow-through sensor block

FEATURES and BENEFITS

- LED light sources for stable long life
- Multiple fluorescence excitation and emission wavelengths available to simultaneously define oil types
- Light Scatter available with or without fluorescence for non-petroleum oils and turbidity
- Cuvet available for manual sample insertion testing
- Scale/Algae Inhibitor module available for untreated waters
- Easy calibration with menu-driven 4-line display
- Sensor block can be remote from controller to 1,200 meters
- Compressed air inlet on sensor block for high condensation applications

SPECIFICATIONS

Range	1-200 ppm or mg/l	Power Input	24vdc or 80-240vac
Accuracy	+/- 1% of calibrated range	Enclosures	Type 4/IP65 coated steel, 316SS or polycarbonate
Resolution	0.15 ppm or mg/l	Ambient Temp.	10-55 C (32-130 F)
Sensitivity	463 ppb crude reference 145 ppb diesel reference	Certified to	Electrical Safety Standards UL/ANSI, CSA, and IEC Standard 61010-1
Process Temp.	0-55 C (32-130 F)		
Pressure to Sensor	minimum 2 psig (14 kPa) maximum 150 psig (690 kPa)		
Flowrate	auto-regulated to 1.0 L/m	<div style="border: 1px solid black; padding: 5px;"> Also available with a purge/pressurization system for Div 2 and Zone 2 installations. </div>	

Arjay Engineering Ltd www.ArjayEng.com +1 (905) 829-2418